


Bamboo Trail


CRP250201



Item no. CRP250201-0901

General Product Information

Dimensions LxWxH	978x97x409 cm
Age group	6+
Play capacity (users)	10
Colour options	  



The Bamboo Trail is a great, versatile play invitation in any playground. Its immense appeal will attract children again and again, to try out the tight, bouncy ropes and the varied climbing options. Many children can play at once on the Bamboo trail thanks to the transparent design. This allows for children to see one another, interact and communicate

through the piece. The Climbing Wall can be used from both sides, supporting cooperative play. The challenging Zig-Zag Slider offers rich training of coordination and muscles, and a firm surface in the bouncy surroundings. The trail sways and bounces back the child's movements, adding an element of thrill and concentration to every step. Climbing here is

great fun and may pave the way to friendships for life.




Bamboo Trail

CRP250201




Zig-zag slider

Physical: muscle strength, balance and coordination when climbing up and down, holding tight.



Climbing wall

Physical: climbing here develops cross coordination, which supports cross-modal perception, necessary for other skills such as reading.



Swaying seesaw

Physical: the Swaying Seesaw is a challenging training of balance, spatial awareness & timing. The skills trained here are fundamental for instance for navigating traffic safely. **Social-Emotional:** passing others on the bridge intensely trains cooperation and communication skills.

Bamboo Trail

CRP250201



Ropes of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester yarn is made from +95% post-consumer materials and is inductively melted onto each strand.




Colored steel components have a base of hot dip galvanization and a powder coated top finish. This provides an ultimate corrosion resistance in all climates around the world. Other steel surfaces are hot dip galvanized inside and outside with lead free zinc.



Corocord smart clamps are carefully designed in every detail to ensure superior flexibility in high quality aluminum material. The smart clamps are attached around the posts with four steel bolts. Not used attachment points are closed with PA caps.


Item no. CRP250201-0901	
Installation Information	
Max. fall height	185 cm
Safety surfacing area	49.0 m²
Total installation time	11.0
Excavation volume	5.72 m³
Concrete volume	3.39 m³
Footing depth (standard)	90 cm
Shipment weight	478 kg
Anchoring options	Surface ✓ In-ground ✓
Warranty Information	
Aluminium Clamps	10 years
Galvanised Steel	Lifetime
Painted Toplayer	10 years
Ropes & Nets	10 years
Spare Parts Guarantee	10 years



Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco-friendly material, which is not only recyclable after use but also consists of a core produced from 100% recycled material.



The rocking tube is made of medium density PE with excellent impact strength and usable within a large temperature span. The longitudinal grooves provide a slip resistant surface for safe play.




The stainless steel components are made of high-quality stainless steel in compliance with global playground standards. The steel is glass blasted after manufacturing to ensure a smooth gliding surface.



Sustainability Data

CRP250201



Cradle to Gate A1-A3	Total CO ₂ emission	CO ₂ e/kg	Recycled materials
	kg CO ₂ e	kg CO ₂ e/kg	%
CRP250201-0901	1,046.70	3.25	45.60

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S
C.F. Tietgens Boulevard 32C
DK-5220 Odense SØ
Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025
Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000





Bamboo Trail

CRP250201

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)