

# Surfer, Hangout


COR29950



Wow! The Surfer is an attractive, swaying meeting point with two lovely Loops. The blue and green Loops invite meetings for two or more children. Their rubbery materials add a soft, gently bouncy feel that children appreciate. The swaying movements gently train the sense of balance. The sense of balance is fundamental to all other movement:

walking, running and even sitting still, which takes trunk stability. So learning at school and concentrating ultimately is hugely promoted with a well-functioning sense of balance. The social-emotional play value of the Surfer is evident: children sit one or two together and have friendly chats. And not least, they enjoy the fact that there is finally a fun playground

meeting point which is designed to meet their need for quirky rests with friends: standing, sitting, lying, kneeling, hanging – and all of it while swaying. A great place for making friends.

Item no. COR299501-0406	
General Product Information	
Dimensions LxWxH	414x191x247 cm
Age group	5+
Play capacity (users)	4
Colour options	



# Surfer, Hangout

COR29950



## Hangout pod

**Physical:** sitting and lying enjoying the swaying movements stimulate the sense of balance. **Social-Emotional:** meeting, taking a break is invited. Turn-taking supports the skills necessary to learn how to avoid conflicts.



# Surfer, Hangout

COR29950



Hangout pod designed with a welded frame of two steel rings which are hot dip galvanized and powder coated. The membrane consist of friction-proof rubberized material of conveyor belt quality with excellent UV resistance.



The steel surfaces are hot dip galvanized inside and outside with lead free zinc. The galvanization has excellent corrosion resistance in outside environments and requires low maintenance.



Corocord aluminium clamps are used as connectors between steel posts and rope. Two aluminium castings are bolted together. The height of the clamps is thus variable.



Ropes of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester yarn is made from +95% post-consumer materials and is inductively melted onto each strand. The ropes are highly wear-and vandalism-resistant and can be replaced at site if needed.



Ground anchoring chains are made of 6mm thick hot dip galvanized steel.

Item no. COR299501-0406

## Installation Information

Max. fall height	34 cm
Safety surfacing area	28.1 m <sup>2</sup>
Total installation time	6.6
Excavation volume	2.11 m <sup>3</sup>
Concrete volume	1.20 m <sup>3</sup>
Footing depth (standard)	110 cm
Shipment weight	363 kg
Anchoring options	In-ground ✓

## Warranty Information

Hot dip galvanised steel	Lifetime
Painted toplayer	10 years
Ropes & nets	10 years
Spare parts guaranteed	10 years
Stainless steel components	Lifetime



# Sustainability Data

COR29950



Cradle to Gate A1-A3	Total CO <sub>2</sub> emission	CO <sub>2</sub> e/kg	Recycled materials
	kg CO <sub>2</sub> e	kg CO <sub>2</sub> e/kg	%
COR299501-0406	889.00	2.75	45.20

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

**Kompan A/S**  
C.F. Tietgens Boulevard 32C  
DK-5220 Odense SØ  
Denmark



### Verification of CO<sub>2</sub> calculation of: Corocord



Data version no. 2023-10-05

The CO<sub>2</sub> calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

**Date: 30. October 2023 | Valid until: 30. October 2025**  
**Verified by:**

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

**Publication date: 30. October 2023**

**By Bureau Veritas HSE**  
www.bureauveritas.dk  
+45 7731 1000




# Surfer, Hangout


COR29950

\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area

\* Max fall height | \*\* Total height



COR299501  
\*34cm  
\*\*247cm  
\*\*\*28.1m<sup>2</sup>



COR299501

[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)