


Fitness Jumper Wobble

FSW234



The fitness jumper is designed to be fun, fun, fun - and of course effective for everybody. When exercisign on a KOMPAN Fitness Jumper, you get an intense cardiovascual workout, you train your balance and improve your bone density. The Fitness Jumper challenges both the experienced fitness jumper athlete and the average fitness enhusiast.

The handlebars offer support for beginnners and adds the possibility to do high intensity power rounds with extra high jumps. By sharing the same post with the Wobble we have created a workout station which is great for imnpoving ankle and knee stability.

Item no. FSW23400-0902

General Product Information

| | |
|-----------------------|----------------|
| Dimensions LxWxH | 192x272x140 cm |
| Age group | 13+ |
| Play capacity (users) | 2 |
| Colour options | |




See KOMPAN Fit app for more




Fitness Jumper Wobble


FSW234




The jumping membranes are made of 6,0mm thick EP Ethylene-Propylene conveyor belt with polyester polyamide fabric carcass. Spring fixations are reinforced with steel bushings and washers on both sides. The membrane is ozone resistant and equipped with 8 center placed water drain holes.




All 36 springs are made of stainless steel to ensure durability and excellent corrosion resistance. The steel wire is 3,2 mm thick and the last five windings are cone shaped to ensure long lifetime of the jumper.



The tiles are molded in grey granulated recycled rubber (SBR/NR), and the KOMPAN logo is made of EPDM Ethylene Propylene Diene Monomer. Inside each of the rubber tiles there is a 3 mm hot dip galvanized steel plate.



All steel components are manufactured from carbon steel S235 in a thickness of 3 mm. Side panels, support walls for top frame, plates bended with SBR and plates flat for in-situ surfacing are hot dip galvanized.



As a unique feature the SBR tiles can be removed for cleaning and service. By loosen six screws the SBR tile can be lifted up to open and gain access to the springs (see instruction on KOMPAN Master).



The double ROSTA element is made of ductile iron and has a hot-dip galvanized finish before painting. The ROSTA element is maintenance-free, with a elastic joint capable of a range of motion up to 250 degrees in any direction. Both wobbles have different stiffness, with a 45% disparity.

Item no. FSW23400-0902

Installation Information

| | |
|--------------------------|-------------|
| Max. fall height | 100 cm |
| Safety surfacing area | 17.5 m² |
| Total installation time | 5.6 |
| Excavation volume | 1.24 m³ |
| Concrete volume | 1.06 m³ |
| Footing depth (standard) | 90 cm |
| Shipment weight | 435 kg |
| Anchoring options | In-ground ✓ |


Warranty Information

| | |
|------------------------|----------|
| Jumper springs | 2 years |
| Jumping bed material | 2 years |
| Post | 10 years |
| ROSTA element | 2 years |
| Spare parts guaranteed | 10 years |



Sustainability Data

FSW234



| Cradle to Gate A1-A3 | Total CO ₂ emission | CO ₂ e/kg | Recycled materials |
|----------------------|--------------------------------|-------------------------|--------------------|
| | kg CO ₂ e | kg CO ₂ e/kg | % |
| FSW23400-0902 | 557.30 | 2.33 | 56.70 |

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S
C.F. Tietgens Boulevard 32C
DK-5220 Odense SØ
Denmark



Verification of CO₂ calculation of: Fitness



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025
Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000




Fitness Jumper Wobble


FSW234

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



FSW23400
*100cm
**140cm
***17.5m²



[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)