





# Kipunji Trail

CRP251001



Item no. CRP251001-0902	
General Product Information	
Dimensions LxWxH	799x681x369 cm
Age group	6+
Play capacity (users)	32
Colour options	  



WOW! The Kipunji's varied range of climb, crawl and bounce thrills makes it highly attractive for children, again and again. The high variety of activities appeal to a wide age range, challenging cross-coordination skills, which again trains body confidence and spatial awareness. The triangular membrane and horizontal nets serve as spacious meeting

points, inviting children to rest and socialize amidst the physical thrills. Kipunji also invites acrobat exercises on the high bars and rocking and swaying upper body driven movements on the Overhead Rocker with UFO discs. This invites cooperation and upper body activity, which is especially important in today's sedentary lifestyles. Kipunji is a highly versatile

play piece that invites both physical and social activity.



# Kipunji Trail

CRP251001




## Curved slide

**Physical:** develops spatial awareness, sense of balance and trains core muscles when sitting upright going down. **Social-Emotional:** empathy stimulated by turn-taking.




## Climbing wall

**Physical:** climbing here develops cross coordination, which supports cross-modal perception, necessary for other skills such as reading.



## Quadrangle amusement net

**Physical:** the inclined net supports the upward climbing movement of the body. Children develop cross-body coordination and muscle strength. **Social-Emotional:** the big net allows for more children being seated or lying together, sharing.



## Triangular net

**Social-Emotional:** the net allows for more children being seated or lying together, sharing.



## Overhead rocker

**Physical:** arm, leg and core muscles climbing up and through. Proprioception and spatial awareness are supported when climbing through. **Social-Emotional:** cooperation when rocking from both sides. Swaying seat for a break, inviting socialising and turn-taking.



## Membrane

**Physical:** the bouncy membrane develops the sense of balance when the child stands, steps or sits here. **Social-Emotional:** great point for a break or meeting with friends.

# Kipunji Trail

CRP251001



Ropes of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester yarn is made from +95% post-consumer materials and is inductively melted onto each strand.



Designed to allow the typical function of rope play structures to move Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector. Our clamps are safe, durable and vandalism-proof.



Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco-friendly material, which is not only recyclable after use but also consists of a core produced from 100% recycled material.



Colored steel components have a base of hot dip galvanization and a powder coated top finish. This provides an ultimate corrosion resistance in all climates around the world. Other steel surfaces are hot dip galvanized inside and outside with lead free zinc.



Corocord smart clamps are carefully designed in every detail to ensure superior flexibility in high quality aluminum material. The smart clamps are attached around the posts with four steel bolts. Not used attachment points are closed with PA caps.



The slide is made of moulded PE, which has excellent impact strength and is suitable for hot climates.

Item no. CRP251001-0902	
Installation Information	
Max. fall height	214 cm
Safety surfacing area	68.0 m²
Total installation time	27.9
Excavation volume	15.72 m³
Concrete volume	8.60 m³
Footing depth (standard)	90 cm
Shipment weight	955 kg
Anchoring options	Surface ✓ In-ground ✓
Warranty Information	
Aluminium Clamps	10 years
Galvanised Steel	Lifetime
Painted Toplayer	10 years
Ropes & Nets	10 years
Spare Parts Guarantee	10 years





# Sustainability Data

CRP251001



Cradle to Gate A1-A3	Total CO <sub>2</sub> emission	CO <sub>2</sub> e/kg	Recycled materials
	kg CO <sub>2</sub> e	kg CO <sub>2</sub> e/kg	%
CRP251001-0902	2,145.80	3.34	45.90

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S  
C.F. Tietgens Boulevard 32C  
DK-5220 Odense SØ  
Denmark



### Verification of CO<sub>2</sub> calculation of: Corocord



Data version no. 2023-10-05

The CO<sub>2</sub> calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025  
Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE  
www.bureauveritas.dk  
+45 7731 1000





# Kipunji Trail

CRP251001

\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area

\* Max fall height | \*\* Total height



[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)