


FSW235




challenging exercises it can be used standing on one foot using one hand – either front facing or sideways.

Exercising on a KOMPAN Fitness Jumper gives an intense cardiovascular workout, you train your balance and improve your bone density. The Fitness Jumper challenges both the experienced fitness jumper athlete and the



Fitness Jumper Flex


FSW235



The jumping membranes are made of 6.0mm thick EP Ethylene-Propylene conveyor belt with polyester polyamide fabric carcass. Spring fixations are reinforced with steel bushings and washers on both sides. The membrane is ozone resistant and equipped with 5 center placed water drain holes.



All 36 springs are made of stainless steel to ensure durability and excellent corrosion resistance. The steel wire is 3,2 mm thick and the last five windings are cone shaped to ensure long lifetime of the jumper.



As a unique feature the SBR tiles can be removed for cleaning and service. By loosen six screws the SBR tile can be lifted up to open and gain access to the springs (see instruction on KOMPAN Master).

Item no. FSW23500-0902	
Installation Information	
Max. fall height	100 cm
Safety surfacing area	16.3 m²
Total installation time	5.9
Excavation volume	1.15 m³
Concrete volume	1.02 m³
Footing depth (standard)	90 cm
Shipment weight	408 kg
Anchoring options	In-ground ✓
Warranty Information	
EcoCore HDPE	Lifetime
Galvanised Steel	Lifetime
Jumper Springs	2 years
Jumping bed material	2 years
Spare Parts Guarantee	10 years



The ball grips are ø80mm and are made from black vacuum formed polycarbonate (PC) which is extremely strong and can withstand high impact.



The bearing house is made from hot-dip galvanised steel. The bearing shaft is made from stainless steel AISI304. The bearing itself is made from polyoxymethylene (POM), an engineering thermoplastic with high stiffness, low friction, and excellent dimensional stability.




The ø800x19mm wheel is manufactured from HDPE EcoCore™, which is a highly durable, eco-friendly material, that is recyclable after use and produced from 100% recycled material. The core has a thickness of 15mm and is representing 80% of the total material.



Sustainability Data

FSW235



Cradle to Gate A1-A3	Total CO ₂ emission	CO ₂ e/kg	Recycled materials
	kg CO ₂ e	kg CO ₂ e/kg	%
FSW23500-0902	476.80	2.17	60.00

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))



Kompan A/S
C.F. Tietgens Boulevard 32C
DK-5220 Odense SØ
Denmark



Verification of CO₂ calculation of: Fitness



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025
Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000




Fitness Jumper Flex


FSW235

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



FSW23500
*100cm
**140cm
***16.3m²



FSW23500

[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)