


Double Somersault Bars

PCM802



Item no. PCM802-0902	
General Product Information	
Dimensions LxWxH	213x65x170 cm
Age group	4+
Play capacity (users)	2
Color options	●



The Double Somersault Bars are great old school playground favourite. They are irresistible to children, and their parents too. The Double Somersault makes for cooperation and sharing in two different heights. They accommodate more users and different age and ability levels. The Double Somersault caters for a range of play activities, hanging the

arms, swaying, training upper body muscles. Sitting on the bars with friends, sharing, using social-emotional skills, or just somersaulting. Somersaulting on the Double Somersault trains children's awareness: the awareness of where body parts are and how to coordinate movements to fit a space. It trains the senses of space and balance too, making the child

able to navigate its surroundings safely. Last, but not least, it is great for training the major muscles.



Double Somersault Bars

PCM802



Somersault bar

Physical: develop balance and core when hanging from knees. Arm, leg and core muscles are developed when climbing up, somersaulting around. Balance and spatial awareness are strengthened. **Social-**

Emotional: meeting, socializing and turn-taking when climbing up and down via bar.



Double Somersault Bars

PCM802



Steel posts are galvanised inside and outside with powder coated top finish. This provides an ultimate corrosion resistance in all climates around the world.



The turnbars are hot dip galvanised inside and outside with lead free zinc. The galvanisation has excellent corrosion resistance in outside environments and it requires low maintenance.

Item no. PCM802-0902	
Installation Information	
Max. fall height	148 cm
Safety surfacing area	14.2 m ²
Total installation time	2.6
Excavation volume	0.08 m ³
Concrete volume	0.03 m ³
Footing depth (standard)	85 cm
Shipment weight	63 kg
Anchoring options	In-ground ✓
	Surface ✓



Sustainability Data

PCM802



Cradle to Gate A1-A3	Total CO ₂ emission	CO ₂ e/kg	Recycled materials
	kg CO ₂ e	kg CO ₂ e/kg	%
PCM802-0902	140.10	3.35	46.50

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

KOMPAN
Let's play

Kompan A/S

C.F. Tietgens Boulevard 32C
DK-5220 Odense SØ
Denmark



Verification of CO₂ calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: GXY916012-3417.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025

Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000




Double Somersault Bars

PCM802


* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



PCM802-xx02

*148cm
**170cm
***14.2m²



PCM802

[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)