

Surfer, Optic

COR29960



The Optic Surfer is a novel sensory activity: a place for visual amazement, wonder and development of logical thinking that attracts children for a playground break. There are three different moiré effects and two dichroic panels. The moiré panels fascinate with the patterns that look different from glance to glance, depending on the eye's focus. Children

report that they get curious about the reason for the patterns behaving differently, and want to debate why not everyone can see the patterns. This provides the opportunity for negotiation, explaining and helping others out. This is great training in cooperation and teamwork that supports these skills in school. The dichroic panels intrigue children with their

color changes, highly depending on the surrounding lights. The rainbow colors throw colorful shadows on the ground and light up friends' faces with their color-changing reflections. The optic panels of the Surfer make children wonder, think and seek explanations for the phenomena they observe.

Item no. COR299601-0406	
General Product Information	
Dimensions LxWxH	13'7"x5'4"x8'3"
Age group	5 - 12
Play capacity (users)	6
Color options	



Surfer, Optic

COR29960



Moiré optic panels

Physical: sitting, hanging and leaning on the rope suspended panels train balance and cross-coordination. **Social-Emotional:** discussing the patterns and reasoning with others supports negotiating and listening skills, training tolerance and empathy. **Cognitive:** wondering about, understanding and explaining the reasons for the patterns supports logical thinking skills.




Dichroic panels

Physical: hanging and leaning on the rope-suspended panels train muscles, balance and cross-coordination. **Social-Emotional:** twisting the panels to create colorful shadows encourages turn-taking and cooperation skills. **Cognitive:** wondering about, understanding and explaining the reasons for the color occurrence supports logical thinking skills.

Surfer, Optic

COR29960



Turnable optic panels of two 7mm thick polycarbonate plates with a distance of 40mm. The inside graphic print consist of an inner image layer and outer transparent protection layer. Both PC panel and the water-based lacquer are UV stabilized to prevent fading of the print.



The steel surfaces are hot dip galvanized inside and outside with lead free zinc. The galvanization has excellent corrosion resistance in outside environments and requires low maintenance.




Corocord aluminium clamps are used as connectors between steel posts and rope. Two aluminium castings are bolted together. The height of the clamps is thus variable.



Corocord ropes of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester yarn is made from +95% post-consumer materials and is inductively melted onto each strand. PES has high strength with excellent resistance to abrasion and UV radiation. The ropes are connected by stainless steel S-Clamps which are pressed around the rope which results in a durable and vandalism

solution.



Please note: Dichroic film is a reflective material. As the sun moves around a product, there will be reflections to the environment around, which can be quite bright when the sun is at a certain angle. But as the sun moves, so will the reflections.


Item no. COR299601-0406	
Installation Information	
Max. fall height	0'0"
Safety surfacing area	0ft²
Total installation time	6.4
Excavation volume	2.98yd³
Concrete volume	1.66yd³
Footing depth (standard)	3'7"
Shipment weight	702lbs
Anchoring options	In-ground ✓
Warranty Information	
Hot dip galvanized steel	Lifetime
Painted toplayer	10 Years
Ropes & nets	10 Years
Spare Parts Availability	10 Years
Stainless steel components	Lifetime

Elevated activities 0	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
Present	0	1	1
Required	0	1	1



Sustainability Data

COR29960



Cradle to Gate A1-A3	Total CO ₂ emission	CO ₂ e/kg	Recycled materials
	kg CO ₂ e	kg CO ₂ e/kg	%
COR299601-0406	1,014.40	3.29	43.10

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S
C.F. Tietgens Boulevard 32C
DK-5220 Odense SØ
Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025
Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000




Surfer, Optic


COR29960

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



COR299601
**8'-3" / 251cm



COR299601

[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)